


Two Core Cu XLPE/PVC Neutral Screen (0.6/1.0kV)

- Standard : AS/NZS 4961
- Voltage, U₀/U : 0.6/1.0kV
- Temperature rating : 90°C
- Conductor : Plain Annealed Copper Wire
AS/NZS 1125, *Class 2*
- Insulation : Cross-linked Polyethylene, X-90
Red, White
- Screen : Plain Annealed Copper Wire
- Sheath : RoHS PVC V-90
Black



Item Code	Conductor		Nom. insulation thickness	Screen		Nom. sheath thickness	Approx. size of cable (H x W)	Approx. cable weight	DC Conductor Resistance @ 20°C	AC Conductor Resistance @ 75°C	Minimum Bend Radius	
	Size	Nom. diameter		Nom. diameter of wire	calculated area						Installed (H/W)	During Installation (H/W)
	mm ²	mm		mm	mm ²						mm	mm
1217910016	2C X 25	6.4	0.9	0.85	25	3.2	16.6 x 25.0	1,060	0.727	0.927	100/150	150/225

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of MM Cables is indicative only and shall not be binding on MM Cables or be treated as constituting a representation on the part of MM Cables.