


Four Core Al XLPE/PVC Circular (0.6/1.0kV)

- Standard : AS/NZS 4026
- Voltage, U₀/U : 0.6/1.0kV
- Temperature rating : 90°C
- Conductor : Aluminium Wire
AS/NZS 1125, *Class 2*
- Insulation : Cross-linked Polyethylene, X-90
Red, White, Blue, Black
- Sheath : RoHS PVC 5V-90
Black, UV Stabilised.



Item Code	Conductor		Nom. insulation thickness	Nom. sheath thickness	Approx. diameter of cable	Approx. cable weight	DC Conductor Resistance @ 20°C	AC Conductor Resistance @ 90°C	Minimum Bend Radius	
	Size	Nom. shaped dimension							Installed	During Installation
	mm ²	mm								
1262993016	4C X 50	7.6 x 10.6	1.0	1.8	27.1	910	0.641	0.822	220	325
1263155016	4C X 70	9.2 x 12.9	1.1	2.0	31.6	1,260	0.443	0.568	255	380
1263170016	4C X 95	11.0 x 15.3	1.1	2.1	35.7	1,640	0.320	0.411	290	430
1263200016	4C X 120	12.4 x 17.3	1.2	2.3	39.8	2,040	0.253	0.325	320	480
1263270016	4C X 185	15.5 x 21.7	1.6	2.6	49.3	3,120	0.164	0.211	395	595
1263280016	4C X 240	17.9 x 25.0	1.7	2.8	55.4	3,980	0.125	0.162	445	665
1263300016	4C X 300	20.1 x 28.1	1.8	3.0	61.3	4,900	0.100	0.130	490	740

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of MM Cables is indicative only and shall not be binding on MM Cables or be treated as constituting a representation on the part of MM Cables.