


Two Core + Earth Cu XLPE/PVC Circular (0.6/1.0kV)

- Standard : AS/NZS 5000.1
- Voltage, U_0/U : 0.6/1.0kV
- Temperature rating : 90°C
- Conductor : Plain Annealed Copper Wire
AS/NZS 1125, *Class 2*
- Insulation : Cross-linked Polyethylene, X-90
Red, Black, Green/Yellow
- Sheath : RoHS PVC 5V-90
Black



Item Code	Phase			Earth			Nom. sheath thickness	Approx. diameter of cable	Approx. cable weight	DC Conductor Resistance @ 20°C		AC Conductor Resistance @ 90°C	Minimum Bend Radius	
	Size	Nom. diameter	Nom. Insulation thickness	Size	Nom. diameter	Nom. Insulation thickness				Phase	Earth		Installed mm	During Installation
	mm ²	mm	mm	mm ²	mm	mm				Ω/km			mm	mm
1219110016	2C X 10	4.1	0.7	4	2.6	0.7	1.8	14.7	380	1.83	4.61	2.33	60	90
1219185016	2C X 16	4.8	0.7	6	3.1	0.7	1.8	16.2	530	1.15	3.08	1.47	65	100
1219270016	2C X 25	6.0	0.9	6	3.1	0.7	1.8	19.4	760	0.727	3.08	0.927	80	120

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of MM Cables is indicative only and shall not be binding on MM Cables or be treated as constituting a representation on the part of MM Cables.