


Three Core Cu PVC/SWA/PVC Circular (0.6/1.0kV)

- Standard : AS/NZS 5000.1
- Voltage, U₀/U : 0.6/1.0kV
- Temperature rating : 75°C
- Conductor : Plain Annealed Copper Wire
AS/NZS 1125, *Class 2*
- Insulation : RoHS PVC V-90
Red, White, Blue
- Bedding : RoHS PVC 5V-90
Black
- Armouring : Single layer of galvanized steel wire
- Sheath : RoHS PVC 5V-90
Black



Item Code	Conductor		Nom. insulation thickness	Bedding		Nom. diameter of armour wire	Nom. sheath thickness	Approx. diameter of cable	Approx. cable weight	DC Conductor Resistance @ 20°C	AC Conductor Resistance @ 75°C	Minimum Bend Radius	
	Size	Nom. diameter		Nom. thickness	Approx. diameter							Installed	During Installation
	mm ²	mm	mm	mm ²	mm	No.	mm	mm	kg/km	Ω/km	Ω/km	mm	mm
1219950016	3C X 1.5	1.5	0.8	1.0	8.8	0.9	1.8	14.2	390	13.6	16.5	170	260
1220195016	3C X 2.5	2.0	0.8	1.0	9.9	0.9	1.8	15.3	460	7.41	9.01	185	275
1220470016	3C X 4	2.6	1.0	1.0	11.9	1.25	1.8	18.0	690	4.61	5.61	220	325
1220560016	3C X 6	3.1	1.0	1.0	13.1	1.25	1.8	19.2	800	3.08	3.75	230	350

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of MM Cables is indicative only and shall not be binding on MM Cables or be treated as constituting a representation on the part of MM Cables.