


Three Core + Earth Cu PVC/PVC Circular (450/750V)

- Standard : AS/NZS 5000.2
- Voltage, U₀/U : 450/750V
- Temperature rating : 75°C
- Conductor : Plain Annealed Copper Wire
AS/NZS 1125, *Class 2*
- Insulation : RoHS PVC V-90
Red, White, Blue, Green/Yellow
- Sheath : RoHS PVC 5V-90
Black



Item Code	Phase			Earth			Nom. sheath thickness	Approx. diameter of cable	Approx. cable weight	DC Conductor Resistance @ 20°C		AC Conductor Resistance @ 75°C	Minimum Bend Radius	
	Conductor		Nom. insulation thickness	Conductor		Nom. insulation thickness				Phase	Earth		Installed	During Installation
	Size	Nom. diameter		Size	Nom. diameter									
	mm ²	mm		mm ²	mm									
1218180016	3C X 1.5	1.5	0.6	1.5	1.5	0.6	1.2	9.0	130	13.6		16.5	40	55
1218520016	3C X 2.5	2.0	0.7	2.5	2.0	0.7	1.4	11.1	210	7.41		9.01	45	70
1218915016	3C X 4	2.6	0.8	2.5	2.0	0.7	1.3	12.4	270	4.61	7.41	5.61	50	75
1219035016	3C X 6	3.1	0.8	2.5	2.0	0.7	1.3	13.4	340	3.08	7.41	3.75	55	80

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of MM Cables is indicative only and shall not be binding on MM Cables or be treated as constituting a representation on the part of MM Cables.