


Four Core Cu PVC/SWA/PVC Circular (0.6/1.0kV)

- Standard : AS/NZS 5000.1
- Voltage, U₀/U : 0.6/1.0kV
- Temperature rating : 75°C
- Conductor : Plain Annealed Copper Wire
AS/NZS 1125, *Class 2*
- Insulation : RoHS PVC V-90
Red, White, Blue, Black
- Bedding : RoHS PVC 5V-90
Black
- Armouring : Single layer of galvanized steel wire
- Sheath : RoHS PVC 5V-90
Black



Item Code	Conductor		Nom. Insulation thickness mm	Bedding		Nom. diameter of armour wire No.	Nom. sheath thickness mm	Approx. diameter of cable mm	Approx. cable weight kg/km	DC Conductor Resistance @ 20°C Ω/km	AC Conductor Resistance @ 75°C Ω/km	Minimum Bend Radius	
	Size	Nom. diameter		Nom. thickness	Approx. diameter							Installed	During Installation
	mm ²	mm		mm ²	mm							mm	mm
1219985016	4C X 1.5	1.5	0.8	1.0	9.6	0.9	1.8	15.0	430	13.6	16.5	180	270
1220260016	4C X 2.5	2.0	0.8	1.0	10.8	0.9	1.8	16.2	520	7.41	9.01	195	295
1220500016	4C X 4	2.6	1.0	1.0	13.1	1.25	1.8	19.2	790	4.61	5.61	230	350
1220590016	4C X 6	3.1	1.0	1.0	14.5	1.25	1.8	20.6	930	3.08	3.75	250	375

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of MM Cables is indicative only and shall not be binding on MM Cables or be treated as constituting a representation on the part of MM Cables.